

HeightBarriers.co.uk Unit 28B Nuralite Industrial Estate, Canal Road, Higham, Kent, ME3 7JA T: 01474 248808

E: sales@heightbarriers.co.uk

Heavy Duty Double Leaf Height Barrier with Swing Gate **HBD-04**

- Double Leaf Heavy Duty Opening Height Barrier system with lockable swing gate
- Ultimate Heavy Duty option providing both strength and security
- Ideal for areas which need a strong steel height barrier which can prevent all access when required.
- Can be locked in the open and closed position
- Ideal for Country Parks, Universities, Schools, Commercial and Industrial sites
- Available in variable width sizes from 6m 12m
- Varying heights options available 1.9m to



Heavy Duty Double Leaf Height Barrier with lockable swing gate. Lockable Swing Gate available in both single or double gate. Height barrier and gate can both be locked in the open and or shut position to provide different access options for vehicles. This provides additional security, especially in areas where there is a need to restrict access after hours, such as a Country Park with closing times.

This is a very popular option with, shopping centres, train stations, local authorities and public car parks. Manufactured from galvanised steel and painted finish to provide a durable and effective product. Optional extras available such as a painted finish, knocking bar, signage, and root fixed or surface fixed options and optional swing gate to prevent access during closing times

SPECIFICATION

Materials: 120 x 120 x 5mm Steel Box Section Top Cross Bar: 60 x 60 x 3mm Steel Box Section Swing Gate: 60 x 60 x 5mm Steel Box Section Finish: Hot Dip Galvanised and or Painted



Surface mounted base plate: 500 x 500 x 10 with gusset steel construction

- ** Opening latch post (strongly recommended) as a safety measure
- ** This product is supplied as Galvanised. If Powdercoated and Galvanised option is selected, this will have an additional cost and will extend the lead time. Please note that this product is not suitable for marine environments unless Galvanised and Powdercoated option is selected.
- ** Bespoke sizes are available and will be made to order. Please choose the next standard size up and specify on your order what exact size you require us to manufacture. Please note that if no bespoke size is selected, the height barrier will be made to the standard size selected.

Optional Extra's: Warning Signage, Knocking Bar, Manual Swing Gate, Opening Latch Post

Installation:

Root Fixed - Recommended size for the concrete foundation is 700x700x700mm deep as a minimum for main posts.

Opening latch post foundation should be a 300mm cube.

Surface Fixed - Main post requires 4 no 16mm bolts for the two upright posts. The base size is 400x400x10mm Catch post requires 4 no 12mm bolts